



PIN NO.	1	2	3	4	5	6	7	8	9
SYMBOL	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0	E1
PIN NO.	10	11	12	13	14	15	16	17	18
SYMBOL	R/W	RS	V0	VSS	VDD	E2	N.C	A(+)	K(-)

NOTE:

1. DISPLAY TYPE:TN(GRAY)
2. DRIVING METHOD: 1/16 DUTY
3. OPERATING VOLTAGE: VDD-V0=4.2V;VLED=5.0V
4. OPERATING TEMP: 0° ~ 50°C
5. STORAGE TEMP: -20° ~ 70°C
6. VIEWING DIRECTION: 12 O'CLOCK
7. POLARIZER MODE: TRANFLECTIVE/POSITIVE
8. CONNECTION: COB
9. CONTROLLER/DRIVER IC:SPLC780D1-001A-C
10. LED BACKLIGHT COLOR:YELLOW-GREEN
11. FRAME MATERIALS:SUS430
12. PROCESS & MATERIALS:ROHS COMPLIANT
13. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE ±0.20MM
14. THE TOTAL THICKNESS OF GLASS IS NOT INCLUDING THE PROTECTIVE FILM.

REVISES								PROJECTION	
CONTENT								CUSTOM	UNITS
	DRAWING BY	沈光娥	2015.07.06	ITEM	COB	SCALE			
	CHECKED BY			CODE	MD260315001	SHEET	1 OF 4		
	APPROVED BY			MODEL	SVC040004FPLB				