


FPC PIN LAYOUT

PIN	NAME
1	CSB
2	RSTB
3	A0
4	D6
5	D7
6	VDD
7	VSS
8	V0
9	X0
10	VG



- NOTE:
1. DISPLAY TYPE:FSTN
 2. DRIVING METHOD: 1/65 DUTY, 1/9 BIAS
 3. OPERATING VOLTAGE: VOP=10.0V,VDD=3.3V
 4. OPERATING TEMP: 0° ~ 60°C
 5. STORAGE TEMP: -20° ~ 70°C
 6. VIEWING DIRECTION: 6 O'CLOCK
 7. POLARIZER MODE: TRANSFLECTIVE-OPTIMAX(DATF)/POSITIVE
 8. CONNECTION: FPC(TIMEX PN:016-802800)
 9. DRIVER I.C.:ST7567
 10. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE ±0.20MM

REVISES CONTENT		SUN-VIEW TECHNOLOGY CO., LTD						
03	增加重點尺寸標示	CUSTOM					PROJECTION	
		DRAWING BY	沈光娥	2018.11.29	ITEM	MO3A087A4	UNITS	mm
		CHECKED BY			CODE	MD121115001	SCALE	1:1
		APPROVED BY			MODEL	SVG063065BWWC	SHEET	1 OF 6